

SMART CRYSTAL™ CINEMA NEO

Polarization modulator for passive 3D



Compact, easy & powerful

- Universal mounting bracket for simple installations
- In 2D mode, panel is safe from dust and impact
- Symmetrical mounting and convenient “boothless” set-up
- High quality 3D images for all seating positions
- Developed and optimized for High Frame Rate content (full comfort HFR)
- Best-in-its-class light efficiency (18%) with projectors up to 7kW
- Designed and engineered in Europe



PERFORMANCE

Recommended installation

Projector type	D-Cinema 3xDLP
Maximum lamp power	7 kW / 32 000 lumens
Screen	Silver - 2.4 minimum gain
Compatible glasses	Passive glasses/clip-on (circular polarization)

Performance

Optical transmission	42%
Stereoscopic contrast	100:1
Technology	Pi-Cell

COMPATIBILITY

3D projectors

DCI*	Yes
3xDLP	Yes
DILA (JVC, DreamVision, Wolf Cinema)	Yes
SXRD (Sony, Mitsubishi...)	No
3xLCD (Epson, Panasonic...)	No
Short focal length	Yes


3D sources

GPIO 37 (3D Cinema)	Yes
GPIO 15	Yes
BNC	Yes
VESA DIN-3	Yes (cable optional)

Frame rates

96 Hz HFR & Home Cinema 3D	Yes
120 Hz Sport HFR & 3D-Ready™	Yes
144 Hz Triple Flash 3D Cinema	Yes
192 Hz Dual Flash HFR	Yes
240Hz	Yes

* Barco, Christie, Cinemeccanica, Kinoton, Nec
** 18% LEF with Volfonni Premium passive 3D glasses



SPECIFICATIONS

Optical

Active surface size	171 x 116mm
Light Efficiency Factor (LEF)	18%**
Dark time (90% Transition)	350µs
Delay time	0µs

Power

Supply	110-240v AC 50/60Hz
Consumption	<40mA AC / 220V

Certification

CE	Yes
ROHS	Yes

Logistics

Operating temperature	+10°C to +40°C (50°F to 122°F)
Storage temperature	-5°C to +50°C (23°F to 122°F)
Relative humidity	from 20% to 80%
Product dimensions (LxWxH)	380 x 254 x 77mm (15 x 10 x 3 in)
Product weight	6 kg (13.2 lbs)
Warranty	3-year

PACKAGING

Composition

SmartCrystal™ Cinema NEO
Bracket
Power cable
BNC/BNC cable
BNC/SUB-D37 cable
BNC/SUB-D15 cable
User guide
Quick start

Weight and Dimensions

Packaging dimensions (LxWxH)	42 x 32 x 25cm
Packaging weight	8kg
Order reference	VPSP-11100